Door stops, holders and silencers

Floor stops and holders

FS18S/FS18L

Floor stop

- FS18S 1 1/2", FS18L 3 1/2"
- Security door stops designed for use in high vandalism areas
- Molded from black flame resistant, resilient material around a heavy-duty stud
- Once grouted in concrete, leaves no exposed fasteners to be tampered with or removed
- Ideal for jail or security cell areas where floor mounted stops are required
- FS18L also ideal for concrete wall applications

Specifications

Material substrate	Made from rubber

Finishes

Black rubber

Dimensions - FS18S

Height	Diameter	Stud length
11/2"	2"	2 1/2"

Dimensions - FS18L

Height	Diameter	Stud length
3 1/2"	2"	2 1/2"



FS18S FS18L

FS434

Floor stop

- For undercut doors up to 1 ½"
- Packed with fasteners for light duty masonry and wood applications
- Soft, resilient black rubber

Specifications

Dimensions

Overall height	Base size
2 5/8"	1 1/2" W x 2 3/4" L

Finish

ВНМА	Description	Substrate	Finish	
604	Zinc Plated	Steel	US2C	

Available accessories

Replaceable soft, resilient black rubber

430

Floor door stop

- For undercut doors up to 1 1/2"
- Welded wood screws for wood applications
- White rubber tip

Specifications

- perintalions	
Material substrate	Made from cast brass
	and aluminum

Dimensions

Overall height	Base size
2 5/8"	1 1/2" W x 2 3/4" L

Finishes - brass

ВНМА	Description	Substrate	Finish	
605	Bright Brass	Brass	US3	
606	Satin Brass	Brass	US4	
609	Blackened Brass	Brass	US5	
613	Oil Rubbed Bronze	Brass	US10B	
619	Satin Nickel	Brass	US15	
625	Bright Chrome	Brass	US26	
626	Satin Chrome	Brass	US26D	

Finishes - aluminum

BHMA	Description	Substrate	Finish	
666	Bright Brass	Aluminum	A3	
_	Blackened Brass	Aluminum	A5	
669	Bright Nickel	Aluminum	A14	
673	Aluminum Clear Coat	Aluminum	A92	

For other colors, consult factory.

Available accessories

Replaceable white or black rubber tips



