

Markar HG315 Edge Mount Hinge Guard

Standard Features

Barrel Type Hinge
 .187" diameter Stainless Steel pin (rod)
 Medical bearings
 Stainless Steel end pins
 Material
 Heavy-duty 14 gauge Stainless Steel
 Finishes
 US32D Satin Stainless Steel (630)
 Standards
 ANSI/BHMA Standard A156.26 Grade 1
 Mounting Hardware
 Fasteners concealed when door is closed
 Custom 12-24 x 1¹/₁₆" S.S Phillips Flat Head Undercut TEK Screws

Capacity
 Supports weights up to 600 lbs.
 4'0" maximum door width
 Standard Sizes
 6'8", 7'0", 7'2", 8'0", 10'0"
 Hole Pattern
 Symmetrically templated
 Handing
 Not required for standard 7'0", 8'0" or 10'0". Specify handing for 6'8" and 7'2" and for most optional features

Fire Rating
 3 hours- hollow metal doors
 90 minutes- hollow metal and composite core wood fire doors
 20 minutes- wood doors



Classified in accordance with UL10C for positive pressure



Fire-rated label


Optional Features

Finishes
 US32 Bright Stainless Steel (629)
 Scratch-Resistant Powder Coated Paint
 Fasteners
 Tamper-proof security screws


Other Features
 Custom lengths- specify in inches
 Custom hole pattern
 Dutch door hinges- suffix "DDP"
 Hospital tips - suffix "HT"
 Raised barrel - suffix "RB"
 Welded end pins
 Security studs

Electrical Modifications
 Adjustable Monitoring Switch - suffix "AMS"
 Current Transfer Prep - suffix "CTP"
 Electrical Transfer Access Prep - suffix "ETAP"
 ElectroLynx®
 EL4 (4 wire), EL8 (8 wire), EL12 (12 wire)
 PoE (9 wire)

Featuring our unique edge guard, this economical hinge prevents objects from being placed between the door and frame as well as protects the door's edge while supporting the door's weight along the entire length of the jamb.



Door Closed



Door Open 180°