

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

8000 Series Surface Mount, Heavy Duty

Standard Features



- Surface mount
- Heavy duty
- **NY SCA approved**
- Stop and hold-open functions available
- Single acting doors only
- Non-handed
- For interior or exterior use on frequent traffic and heavy weight doors
- Standard installation from 85° to 110° of opening (5° increments)
- Shock absorbing spring provides 3° to 5° cushion before dead-stop
- Standard fasteners supplied with sex bolts for 1-3/4" to 2-1/4" thick door (see options for other door thicknesses)
- UL Listed as Miscellaneous Fire Door Accessories for use on wood fire doors rated up to 90 minutes and metal fire doors rated up to 3 hours (stop function only)
- Average weight per unit = 5 lbs.

Options Available

(see page B-5 for details)

- **THICK** - Fasteners for doors other than 1-3/4" to 2-1/4" thick - Specify door thickness
- **SEC** - Security fasteners
- **AJB** - 90541 Angle jamb bracket for push side flush mount
- **LL** - For lead-lined door applications
- **LS** - Less shock-absorbing spring for special applications
- **HD** - Extra heavy duty application - Two additional sex bolts and fasteners provided for door
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

- **Stainless steel** is the standard base material for arm, channel and jamb bracket for all finishes.

Door Frame Opening		Model Number	
Hinges or Offset Pivots	Center Hung	Hold Open	Stop
27" - 32-7/16"	29-1/2" - 34-15/16"	8010	8020
32-1/2" - 38-11/16"	35" - 41-7/16"	8011	8021
38-3/4" - 42-7/16"	41-1/2" - 44-15/16"	8012	8022
42-1/2" - 54"	45" - 56"	8013	8023
ANSI Code		C03511	C03541

Specify When Ordering

- Model Number
- Finish
- Option(s), if applicable

