

Hinges and pivots

Pin and barrel continuous hinges

715

Full mortise, half wrap pin and barrel continuous hinge (stainless steel)

- Half wrap edge guard
- 1/4" diameter pin with nylon self-lubricating, medical grade split bearing
- For doors weighing up to 300 pounds without reinforcing, 600 pounds with reinforcing
- 1/16" door inset
- 48" Maximum door width
- Non-handed, handing required for custom cut lengths
- Square edge door

Specifications

Standard length	83", 85", 95", 120"
Material substrate	14 Gauge type 304 stainless steel
Standard mounting hardware	<ul style="list-style-type: none">▪ #10 X 1/2" Self drilling, self tapping screws▪ #10 X 1" Wood screws
Certifications	<ul style="list-style-type: none">▪ Meets ANSI/BHMA 156.26▪ UL10C listed (3 hour)

Options

CON	Allegion Connect
EPT	Electric power transfer
HT	Hospital tip
TW8	Electrical through-wire

Optional mounting hardware

SECHM	Security screws - hollow metal door and frame
SECWDHM	Security screws - 1/2 wood, 1/2 hollow metal
SECWDWD	Security screws - wood door and frame
WD	Wood door and frame

Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless Steel	Stainless steel	US32D

Custom paint available on 600 Series, consult factory

For single door applications:

For pairs of doors see chart and general information.

