

## Door stops, holders and silencers

### Floor stops and holders

# FS446/FS450

## Floor stop and manual door holder

- Manual type floor holder ideal for interior or exterior use
- Accommodates door undercut up to 2 1/2"
- Replaceable black non-marring rubber tip
- Unit functions as a stop but serves as a hold-open device when hook is manually engaged in strike. Unit requires manual disengagement to release hold-open
- FS446 is packed with fasteners for heavy duty masonry applications
- FS450 is packed with fasteners for drywall/wood applications

### Specifications

Material substrate	Made from cast brass and aluminum
Certifications	<ul style="list-style-type: none"> <li>FS446 Meets ANSI/BHMA 156.16, L11371 for brass and L31371 for aluminum</li> <li>FS450 Meets ANSI/BHMA 156.16, L11361 for brass and L31361 for aluminum</li> </ul>

### Dimensions

Overall height	Height from floor to stop center line	Stop diameter	Base diameter
3 3/4"	2 5/8"	1 1/16"	2 1/2"

### Finishes - brass

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
619	Satin Nickel	Brass	US15
622	Matte Black	Brass	BLK
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D
-	Aged Bronze	Brass	643e/716

### Finish - aluminum

BHMA	Description	Substrate	Finish
628	Satin Aluminum	Aluminum	US28

For other colors, consult factory.

### Available accessories

- Replaceable black non-marring rubber bumper

# FS495/FS496/FS497

## Stops and semi-automatic holders

- FS495 wall stop, FS496 floor stop - 3/8" max clearance, FS497 floor stop - 1" max clearance (all with automatic holders)
- Automatic door holders ideal for heavy-traffic situations that require a simple, hold-open device
- Recommended installation is holder on door and strike on wall
- Holder position on door is adjustable
- Holder is tapered to prevent "child riding"
- Packed with fasteners for heavy duty masonry and drywall/wood applications

### Specifications

Material substrate	Made from cast brass
Certifications	<ul style="list-style-type: none"> <li>FS495 Meets ANSI/BHMA 156.16, L11291 for brass</li> <li>FS496 Meets ANSI/BHMA 156.16, L11301 for brass</li> <li>FS497 Meets ANSI/BHMA 156.16, L11301 for brass</li> </ul>

### Dimensions

- FS495 Holds door 3 3/4" from wall
- FS496 Door to floor clearances 3/8" max
- FS497 Door to floor clearances 1" max

### Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606*	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

\*Not available on FS496 and FS497. For other colors, consult factory.



FS446



FS495