



Application

- Interior or exterior doors
- Doors are single acting
- Non-handed
- Recommended for high traffic, heavy abuse installations

Features

- Heavy-duty
- Slide track design
- Heavy shock absorber spring provides 5-7° compression before deadstop
- LS option omits spring for special application
- On/off knob on hold open models
- Stop, friction stay or hold open function
- Complete screw packet with thru-bolts for door, wood and machine screws for frame
- Torx® screws optional for security applications
- Standard architectural finishes
- Durable slider cam and shock block
- 110° maximum opening
- 1-3/4" minimum door thickness
- 1-3/16" square channel
- For pull side mounting or flush mounting on push side or for rabbeted push side use angle jamb bracket adapter 5458-LH or 5459-RH
- Hanging means other than standard butts or offset pivots require special templating

Compliance

- ANSI/BHMA A156.8, Grade 1 Certified (Hold Open, Stop Models)
- Stop function UL listed for fire door assemblies

DOOR OPENING CHART (IN INCHES)

| Butts Offset Pivots | Center Hung Pivots | Model Number | | |
|---------------------|--------------------|--------------|-------|-------|
| | | Friction | H.O. | Stop |
| *24 - 28 | 25-1/2 - 30 | 9-116 | 9-126 | 9-136 |
| 28-1/16 - 33 | 30-1/16 - 36 | 9-216 | 9-226 | 9-236 |
| 33-1/16 - 38 | 36-1/16 - 41 | 9-316 | 9-326 | 9-336 |
| 38-1/16 - 43 | 41-1/16 - 46 | 9-416 | 9-426 | 9-436 |
| 43-1/16 - 48 | 46-1/16 - 50 | 9-516 | 9-526 | 9-536 |

*Butt hung only on this size door. No swing clear hinges.



Experience a safer and more open world