

Standard Duty Surface Mounted OH1000 Series

Material: Stainless steel Finishes: US32D, US10B

Fasteners: Jamb: #12 x 1¹/₂" FH WS or #12-24 x ¹/₂" FH MS

Door: #12-24 x 11/2" FH MS and 5/16" dia. sex bolt

Features: • Single acting doors

• Non-handed

• Slide track design

• Recommended for medium traffic, medium weight doors

• Degree of opening fully adjustable and can be adapted to changing needs

• Heavy shock absorber spring provides compression before deadstop

• Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in field. MF5012 KIT (Adapter kit) included

• Complete screw packet with thru-bolts for door, wood and machine screws for frame

• Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications

Durable slider cam and shock block

• 110° maximum opening

• 3/4" square channel

• Stop function UL listed for fire door assemblies

• For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000

		Door Opening			
No.	Function	Butts/Offset Pivots	Center Hung	Weight	ANSI A156.8
OH1001S	Stop only	18" - 24"	21" - 261/2"	3.5 lbs.	C05542
OH1002S	Stop only	241/16" - 30"	269/16" - 32"	3.5 lbs.	C05542
OH1003S	Stop only	301/16" - 36"	321/16" - 38"	3.5 lbs.	C05542
OH1004S	Stop only	361/16" - 42"	381/16" - 45"	3.5 lbs.	C05542
OH1005S	Stop only	421/16" - 48"	451/16" - 48"	3.5 lbs.	C05542
OH1001M	Multi-function	18" - 24"	21" - 261/2"	3.5 lbs.	_
OH1002M	Multi-function	241/16" - 30"	26 ⁹ /16" - 32"	3.5 lbs.	_
OH1003M	Multi-function	301/16" - 36"	321/16" - 38"	3.5 lbs.	-
OH1004M	Multi-function	361/16" - 42"	381/16" - 45"	3.5 lbs.	-
OH1005M	Multi-function	421/16" - 48"	451/16" - 48"	3.5 lbs.	_

